

Technical Specification

Product Code
Description:

ECSPK1 Smart Security Kit 1





Kit Part: Smart Hub

General Information Sounder Output 95dB Maximum Devices 32 Kit Warranty 1 Year Transmission Router Transmission Router Transmission Range Auxilliary GSM GSM Frequency Construction ABS Material Fixing Colour Programming Available Operations

2.4GHz (IEEE 802.11 b/g/n) 150m (Open Field)

Yes; Full-size SIM 850 / 900 / 1800 / 1900 MHz

Surface White

433 MHz

Home/Arm/Disarm/SOS

Kit Part: Remote Control

Transmission Frequency Transmission Range Material Colour Available Operations Operating Voltage (DC) Consumption Power Reserve Battery Type Operating Temperature Relative Humidity Dimensions Weight

80m (open field) ABS Black Home/Arm/Disarm/SOS 3V (CR2025 Battery) <7mA Approx. 12 Months CR 2025 -10°C - 55°C <80% (non-condensing) 57mm x 31mm x 11mm 20g

Kit Part: PIR

Т

Number of PIRs	1
PIR Range	8m
Fransmission Frequency	433 MHz
Transmission Range	80m (open field)
Material	ABS
Fixing	Surface
Colour	White
Zone Types	Normal Sensor/24h mode/Delay mode/Home mode/24h mute sensor/Home delay mode
Operating Voltage (DC)	3V (2 x AA Batteries)
Consumption	0.0095A
Power Reserve	Approx. 12 Months
Battery Type	3 x AA (LR06)
Weight	46g
Operating Temperature	-10°C - 55°C
Relative Humidity	<80% (non-condensing)
Dimensions	107mm x 53mm x 32mm
Bracket Dimensions	52mm x 30mm x 26.5mm

Kit Part: Door/Window Contact

433 MHz
80m (open field)
ABS
Surface
White
Normal Sensor/24h mode/Delay mode/Home mode/24h mute sensor/Home delay mode
3V (CR2477)
0.015A
Approx. 12 Months
CR2477
-10°C - 55°C
<80% (non-condensing)
55.7mm x 30.3mm x 16mm
25mm x 10mm x 9mm
20g

Components Supplied

Fort Hub, Fort PIR, Fort Door/Window Contact, Fort Remote Control, AC Adapter, Product Batteries, Mounting Screws & Wall plugs, User Guides